



**WATERITE TECHNOLOGIES, INC.**  
1-885 Keewatin Street  
Winnipeg, MB  
Canada R2X 2S7  
PHONE: (204) 786-1604  
FAX: (204) 783-1599  
Email: [waterite@waterite.com](mailto:waterite@waterite.com)  
Website: [www.waterite.com](http://www.waterite.com)

**WATERITE TECHNOLOGIES, INC.  
PRODUCT SPECIFICATION SHEET  
FIL-CBC-001R1**

**ACTIVATED CARBON BLOCK FILTER  
CARTRIDGE FOR CYST REDUCTION**

<b>TYPE:</b>	2 1/2" cartridges for 10" standard housings
<b>FEED:</b>	Municipal or well water
<b>FEED PRESSURE:</b>	125 psi maximum
<b>TEMP. RANGE:</b>	4.4°C to 77°C
<b>CAPACITY:</b>	74,800 L @ 3.8LPM (chlorine reduction) @ 1GPM
<b>MICRON RATING:</b>	0.5 micron nominal
<b>BODY MATERIAL:</b>	Cartridge end caps: molded polypropylene Netting: polyethylene
<b>CARBON:</b>	Bonded PAC
<b>GASKET:</b>	BUNA-N, low durometer
<b>MODEL:</b>	<i>Excelpure</i> CBC05



***Additional information:***

- Carbon block cartridges normally release a small amount of carbon fines upon first use. After installation, new cartridges should be flushed until all traces of carbon fines are eliminated.
- Estimated capacity based on 2ppm FAC continuous flow @ > 90% chlorine reduction.
- ΔP 3.8 psi @ 1GPM, ΔP 7.7 psi @ 2 GPM
- Nominal rating 85%+ for particles of given size.

***Excelpure*™**

**SPEC FIL-CBC-001R1**

*June, 2005*