



Automatic Flush Valve



AFV Series

Automatic Flush Valve Specifications:

- Adjustable cycle time 5 min - 24 hours
- Working Pressure 200 PSIG
- Ambient Temperature 25 °F to 165 °F
- Enclosure Nema 4
- Voltage 115V, 1 Phase, 60 Hz
- Current 2.5 Amps
- Valve Construction Brass
- Seals Reinforced Teflon
- Discharge Volume 1/2" NPT-.92
(Gal per cycle @ 30 PSIG)
- Power Cord 8' heavy duty grounded
- Full Port Ball Valve 1/2" NPT
- Discharge Time 3.5 seconds
(Non-adjustable)



Automatic Flush Valve Kit Includes:

- (2) 1/2" barb x 1/2" NPT male hose fittings
- (2) SAE size 8 SS worm drive clamps
- (24") 1/2" braid reinforced flexible PVC tubing. (Rated at 215 psi)

KIT DOES NOT INCLUDE FILTER OR AUTOMATIC FLUSH VALVE.

Please Note: TO insure optimum performance of automatic flush valve, it is recommended that you use the above rated tubing only.

Part Number	Description	Ctn Qty	List Price
AFV	Automatic Flush Valve	1	\$ 789.66
AFV-KIT	Automatic Flush Valve Kit	1	46.52

Warranty and Disclaimer

A one year warranty applies to the original purchaser. The manufacturer warrants that the AFV will be free from original defects in material and workmanship.

Manufacturer will **repair or replace** all parts without charge, found to be defective under normal use and service within the warranty period upon return of product at customer's expense.